

DECLARATION OF PERFORMANCE
No. 00013/106/ES

1. Unique identification code of the product-type: 106

Type, batch or serial number or any other element allowing identification of the construction product:
Lightweight fine grained viscous building putty for internal use AT.MIC. The year and day of manufacture is included.

2. Intended use or uses of the construction product, in accordance with the applicable technical specification, as foreseen by the manufacturer:

Light, easily filling, ready-mixed building spackle. Intended applications. The spackle is used for interior finishing of buildings: smoothing out of concrete, plastered, plasterboard and other types of mineral surfaces prior to painting with water-dispersible paint and wallpaper hanging. Recommended for a finishing layer.

3. Declared performance

<i>Essential characteristics</i>	<i>Performance</i>
Putty appearance	White viscous mass
Grinding fineness, %- remainder on sieve 0,020 mm on sieve 0,315 mm	14,0-15,0 0
Polishing	Easy polish, no spot
Consistence, mm	20 - 30
Shrinkage (0,5 mm thickness)	Without cracks after 24 h
Workability	Easy smooth out, very adhesive
Drying time,h(0,5 mm thickness)	2,0-3,0

4. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 3. This declaration of performance is issued under the sole responsibility of the manufacturer. Signed for and on behalf of the manufacturer by:

Sales/business Manager

CompanyAddress:
LAS SUITE, 5 PERCY STREET,
FITZROVIA, LONDON, W1T 1DG, UK
e-mail: ampersands@mail.com
skype: ampersands.corporation
Tel.: +44 20 3290 7779
Fax.: +44 20 3163 1853

Bank Details:
Bank Address:
NatWest Bank
Covent Garden,34 Henrietta Street
London, WC2E 8NL, Great Britain
Account Details: IBAN: GB76NWBK60500035653264
BIC (SWIFT): NWBKGB2L

